

Professional washer extractors



General characteristics

- High-spin floating washer extractors. Do not need to be anchored to the floor.
- Tank with 4 detergent compartments.
- 2 standard water inlets.
- Equipped with variable-frequency drive (standard 50-60 Hz). Balancing system controlled by the same drive.
- Model with drain valve (V) and model with drain pump (P).
- Model with valve specially designed for washing mops.
- Includes leveller feet.
- CE and WRAS product certifications.

Options:

- Double drain (only valve model).
- Drain pump kit.
- Drain normally closed "NC". In case of power failure, the water stays inside the tank.
- 6 extra signals for dosing: a total of up to 14 available.
- Silicone door seal.
- Door with opposite opening.
- Delayed door opening, in case of power failure.





- Unit in AISI 304 stainless steel.
- Plinth that facilitates access to the machine.
- Special mop plinth (with filter) - valve models only.
- Plinth and water recovery tank.
- Kits for self-service: Pay station, token mechanism, coin mechanism.
- Voltage 110 1N 50/60 Hz.
Voltage 440 3~ (No N) 50/60 Hz.
- Connectivity.

Models

- STANDARD Code 19: Use this code for orders of machines that do not include any option or version different from standard.
The retail price is the one indicated in the table.

- Code 18 WITH OPTIONS: Use this code for orders of machines that include some option or options from the OPTIONS ON DEMAND table.

- The retail price is calculated by adding the price increases for each option to the retail price of the standard code.

MODEL	CODE 19 (STANDARD)	CODE 18 (WITH OPTIONS)	DRAIN	HEATING	CAPACITY KG	SPEED		POWER*		DIMENSIONS (MM)	€
						R.P.M.	G	(KW)	(V)		
 LAP-08 TP2 E V	19053089	18001733	Valve	Electric	8	1,250	430	6.25	T	680x698x1,040	-
 LAP-08 TP2 E P	19053091	18001734	Pump	Electric	8	1,250	450	6.25	T	680x698x1,040	-
LAP-08 TP2 HW V	19053094	18001735	Valve	Hot water	8	1,250	450	0.75	M	680x698x1,040	-
LAP-08 TP2 HW P	19053095	18001736	Pump	Hot water	8	1,250	450	0.	M	680x698x1,040	-
 LAP-10 TP2 E V	19052197	18001690	Valve	Electric	10	1,250	450	6.25	T	680x742x1,040	-
 LAP-10 TP2 E P	19053083	18001730	Pump	Electric	10	1,250	450	6.25	T	680x742x1,040	-
LAP-10 TP2 HW V	19053085	18001731	Valve	Hot water	10	1,250	450	0.75	M	680x742x1,040	-
LAP-10 TP2 HW P	19053088	18001732	Pump	Hot water	10	1,250	450	0.75	M	680x742x1,040	-

(*) **M:** Single-phase model.
Can be converted to:
- 230 V III (Three phase) (50-60 Hz).
- 400 V III +N (Three phase) (50-60 Hz).

T: Three-phase model 230 V III / 400 V III +N (50-60 Hz).
Can be converted to: 230 V 1+N (Single-phase) (50-60 Hz).