

Bac Gastronorme Rectangulaire





Chauffage	Modele	Capacité lt.	Dim. Exterieures mm	Dim. Cuve Ø i x h mm	Puissance (kW)		Consommation			
					Gas	Elet.	G.P.L. kg/h	Metano H m3/h	Metano L m3/h	Vapore kg/h
GD DIRECTE	PGN GD280	280	1400x900x850	1040x550x515	35	-	2,76	3,70	4,31	-
IG INDIRECTE	PGN IG180	180	1000x900x850	740x550x515	29	-	2,29	3,07	3,57	-
	PGN IG280	280	1400x900x850	1040x550x515	35	-	2,76	3,70	4,31	-
	PGN IG400	400	2000x900x850	1700x550x515	45	-	3,60	4,80	5,50	-
V VAPEUR	PGN V180	180	1000x900x850	740x550x515	-	-	-	-	-	65
	PGN V280	280	1400x900x850	1040x550x515	-	-	-	-	-	85
	PGN V400	400	2000x900x850	1700x550x515	-	-	-	-	-	115
IE INDIRECTE	PGN IE180	180	1000x900x850	740x550x515	-	18	-	-	-	-
	PGN IE280	280	1400x900x850	1040x550x515	-	24	-	-	-	-
	PGN IE400	400	2000x900x850	1700x550x515	-	36	-	-	-	-