


308A - 307A - 308S

CRI-CRI



TECHNICAL FEATURES

	308A	307A	308S
Dimensions in mm.	685x200x380	685x200x380	685x200x380
Weight	8,6 Kg	8 Kg	11 Kg
Power Supply	230V 50 Hz	230V 50 Hz	230V 50 Hz
Zapping Power	5000V	5000V	5000V
Total Consumption	95W	65W	95W
Lamps UV-A	2X40W	2X20W	2X40W
Lamp Life	2000 h	2000 h	2000 h
Standard equipment	metal chains	metal chains	metal chains
IP Rate	IPX4	IPX4	IPX4
Insulating Class	I	I	I
EAN Code	8010114308017	8010114307010	8010114308048
SPARE LAMPS	0802	0512	0802



Recommended for **medium-size areas**, this model combines **compact size and strength**.


Item **309** is equipped with 2 UV-A actinic lamp of 15 W each and it is effective in a range of about 10-12 linear meters. This item is available also at 15 W (1 lamp instead of 2) with a range of action of 8-10 linear meters.

Both item **309** and **304** emit a 5000 Volt discharge. The grids maintain their efficiency over time because the high voltage discharge zap insects quickly, what is more the electrified slats are designed to prevent insects from sticking.

IPX3 water protection makes it suitable for protected outdoor area as well.



HIGH TENSION INNER GRILLE
5000V POWER OF DISCHARGE
 1. SAFETY SWITCH
 2. GROUNDED EXTERNAL GRID



IPX3

46

