



## PL412H31G0 - FriFri Precision 412 Electric Free-standing Single Tank Fryer - 2 Baskets - W 400 mm - 22.0 kW

For the chef who wants superb temperature control for consistently excellent results, a free standing Precision 412 is the fryer of choice.

- ✔ Electronic temperature control and powerful elements maintains oil to within +/- 1 °C of the temperature selected, reducing oil usage and ensuring your food always has that all-important crunch.
- ✔ With one cooking programme, perfect for when you want to cook the same product time after time, to the same exacting standards.
- ✔ Digital timer displays the count down, with a buzzer sounding at the end of the cook cycle.
- ✔ Temperature view shows current oil temperature, enabling you to make an informed decision as to when to start cooking.
- ✔ Are there more fries than last time? Adaptive cooking automatically adjusts the cooking times to suit your batch size ensuring you never serve undercooked food.
- ✔ Keeping your oil in peak condition! Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- ✔ Raising food to the next level. Perfect for kitchens where you don't have time for constant supervision, optional LiftFri© automatic basket lifting system lifts food at the end of the cycle to prevent overcooking.
- ✔ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.

### Specifications

#### Summary

<b>Brand</b>	FriFri
<b>Range</b>	Precision
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105122258

#### Power and Performance

<b>Total Power kW</b>	22.0
<b>Temperature Range °C</b>	60-190
<b>IP Rating</b>	IPX4
<b>Temperature Control</b>	Electronic

#### Key Specifications

<b>Number of Baskets</b>	2
<b>Number of Tanks</b>	1
<b>Gravity Filtration</b>	Yes
<b>Pumped Filtration</b>	No
<b>Drain Location</b>	Through the body

#### Capacity

<b>Product Output per Hour</b>	44kg fries - 7mm [frozen]
<b>Capacity Litres</b>	17.0-20.5

## Weights and Dimensions

Unit Height (External) mm	994
Unit Width (External) mm	397.5
Unit Depth (External) mm	650
Net Weight Kg	69

## Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	22,000
Three Phase Amps	L1=31.9; L2=31.9; L3=31.9
Three Phase Voltage	400
Number of Supply Cables	1

## Shipping

Packed Weight Kg	69.41
Packed Height cm	113
Packed Width cm	79
Packed Depth cm	52

## Available Options

## Oil Pump

OP1	1 Oil Pump
-----	------------

## Basket Lift

OL1	1 Basket Lift
-----	---------------

## Baskets

411_1_BASKET	1 Basket
411_2_BASKETS	2 Baskets

## Legs/Castors

OC200	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]
OC400	OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]

## Available Accessories

FZ411048	LARGE BASKET FOR 411 - 5MM MESH - COMPLETE WITH HANDLE
----------	--