

SQ1021AMVN0

GAS COMBI OVEN 10 TRAYS GN 2/1 or 660 x 460* - 20 TRAYS GN 1/1 MECHANICAL CONTROL

FUNCTIONAL CHARACTERISTICS	
Display	Analogic
Supply	Natural gas / GPL
Timer	Linear
Number of motors	3
Motor speeds	2
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50mm open
Humidification	Direct injection
Air injection	-
Version	Standard

*Special tray rack support on request

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

STANDARDS		
Certification		CB - GAR
TRAYS		
Trays rack		Sheet GA-BIV 10/80
Max tray load		4kg
DIMENSIONS		
Oven size with handle WxDxH		964 x 1208 x 1321 mm
Oven size without handle WxDxH		964 x 1143 x 1321 mm
Chamber size WxDxH		660 x 770 x 948 mm
Unit weight		164kg
PACKAGING		
Packaging		Pallet + carton box
Packaging size WxDxH		1045 x 1245 x 1422 mm
Unit weight with packaging		187kg
Crate packaging size (optional)		1045 x 1245 x 1414 mm
ELECTRICAL DATA		
	50Hz	**60Hz**
Power	0,58kW	0,79kW
Frequency	50Hz	60Hz
Power supply	220-240V 1N~	220-240V 1N~
Amperage	2,64A	3,59A
Power cord req.	3G1,5	3G1,5
BURNER DATA		
G30 - G31		
G30 - G31 Power		20kW
G30 - G31 Consumption		1,58kg/h
Injector 28...30 mbar		160R
Injector 30 mbar		160R
Injector 37 mbar		150R
Injector 50 mbar		140R
G20		
G20 Power		20kW
G20 Consumption		2,12kg/h
Injector 13 mbar		250R

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it

Injector 20 mbar	225R
Injector 20...25 mbar	225R
Injector 25 mbar	225R
WATER CONNECTION REQUIREMENTS	
Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	8mm quick fitting
Water drain	30mm
Max water hardness	5°f
Water pressure requirement min-max	150-200kPa
CONSUMPTION	
Humidification Water	22,4l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Wi-Fi	STANDARD
Cloud	STANDARD
ACCESSORIES	
Nozzle kit	85BRU00019 (GAS03)
Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	-
External Core probe	-
Sous vide probe	-
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	-

Water softner cover	WS10
Water softner 6800l	WS11
Water softner 12000l	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6kg	DT2
Detergent 10kg	DT4

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it


◆ Standard ◇ Optional - Not available


TYPE OF COOKINGS	
Convection cooking	30°C - 260°C / 86°F - 500°F
Combi cooking	30°C - 230°C / 86°F - 446°F
Steaming cooking	30°C - 130°C / 86°F - 266°F
Static cooking	-
Delta T cooking	-
Core probe cooking	-
Sous vide cooking	-
Low temperature cooking	-
DISPLAY AND CONNECTIVITY	
Type of display	ANALOGIC
Multi-language display	-
Unit set F° or C°	◇
Venix cloud	-
Wi-fi	-
Ethernet port	-
Web server	-
Usb port	-
SETTINGS	
Infinity time set	◆
Chimney set	OPEN
Fan speed set	2
Dehumidification set	-
Humidity set	0-100%
Preheat set	MANUAL
RECIPE COOKING	
User recipes book	-
Factory recipes book	-
Cooking cycles	-
Recipes with name and picture	-
Fast recipe selection buttons	-
SPECIAL CYCLE	
Multi-level mix ALL IN	-
Multi-level mix ALL OUT	-
Food regeneration	-
Overnight cooking	-
Overnight self clean	-
Cook & hold	-


VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it


Multi-timer	-
Routine program	-
Proofing	-
Fast Cooling	-
Automatic washing system / Rinse	-
Fast start	-
Recipe scheduling	-
Holding / Mass production	-
TECHNICAL FEATURES	
Cooking chamber material	AISI 304
Second core probe	-
Insertion of the trays	HORIZONTALLY
Fast loading Pro	-
Glass door	DOUBLE
Easy clean internal glass	◆
High performance thermal insulation	YES
Break drop nebulizer	◆
Lightning	LED ON THE DOOR
Direct injection humidification	◆
Boiler humidification	-
Opening door	NOT REVERSIBLE (RIGHT HANDLE)
Reversing fan	◆
Heavy duty reversing fan	◆
Phase cut speed control	-
Inverter speed control	-

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it









02.	TIMER SELECTOR
03.	TEMPERATURE SELECTOR
04.	LIGHT ON/OFF HEATING ELEMENT
06.	WATER IN-LET SOLENOID VALVE G3/4" (HUMIDIFICATION)
07.	UNIPOTENTIAL TERMINAL
08.	COMPRESSION CABLE GLAND
09.	HOT VAPOUR CHIMNEY Ø50MM (1,97")

11.	LIGHT ON/OFF STEAM
12.	STEAM SELECTOR
13.	DRAIN PIPE Ø30MM (1,18)
17.	TWO SPEED REGULATION BUTTON
33.	SAFETY THERMOSTAT
45.	RESET BURNER
46.	GAS IN-LET G1/4"
47.	HOT FUMES CHIMNEY Ø120MM (4,72")

VENIX SRL Via della Fornace, 49 - 31023 Castelminio di Resana (TV) - ITALY
P +39 (0) 423 420 477 / +39 (0) 423 723 608 - F +39 (0) 423 492 307
email: info@venix.it
www.venix.it