

all photos must be considered as a reference - fotografías no contractuales

STANDARD	
-2°C +8°C	R290
-20°C -15°C	R290

## Armario SNACK 340 L /750 L, refrigeración y congelados SNACK 340 L /750 L cabinet, chiller and freezer



ACRV-55  
ACCV-55



ACRV-125  
ACCV-125

mod.	rango range °C	largo length (mm)	alto height (mm)	fondo depth (mm)	estantes shelves	pares de guías sets of slides	volumen capacity (L)	voltaje voltage	refrigerante refrigerant	potencia frig. frig. power W	potencia power W	clase 2015/1094 EN16825
ACRV-55	-2°C +8°C	540	2075	730	4	4	409	230V-50Hz	R134a*	304	308	4 30°C 55%
									R290	271	213	4 30°C 55%
ACRV-125	-2°C +8°C	1250	2075	665	8	8	964	230V-50Hz	R452A*	668	638	4 30°C 55%
									R290	543	434	4 30°C 55%
ACCV-55	-20°C -15°C	540	2075	730	4	4	409	230V-50Hz	R290	385	445	4 30°C 55%
									R452A*	353	465	4 30°C 55%
ACCV-125	-20°C -15°C	1250	2075	665	8	8	964	230V-50Hz	R290	833	828	4 30°C 55%
									R452A*	534	538	4 30°C 55%

\*opcional - optional

Características técnicas y constructivas sujetas a variación sin previo aviso.

- Exterior en acero inox AISI-304, excepto el respaldo
- Interior en acero inox AISI-304, con aristas curvas y fondo embutido
- Puertas de apertura reversible, con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- ACRV / ACCV doble cristal
- Luz interior LED
- Estantes interiores de alambre en acero plastificado, regulables en altura
- Pies en tubo de acero inox ajustables en altura 135 - 200 mm
- Cuadro de mandos y rejilla ventilación motor, desmontables
- Unidad condensadora ventilada
- Evaporador sistema tiro forzado, con recubrimiento epoxi anticorrosión
- Paro ventiladores tiro forzado al abrir la puerta
- Evaporación automática del agua de descarche
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m<sup>3</sup>, cero efectos ODP y GWP
- Control digital de temperatura, descarches optimizados, alarma por puerta abierta y alta temperatura de condensación. Eficiente gestión del consumo de energía
- Temperatura de trabajo a 32°C ambiente

We reserve the right to change specifications without prior notice.

- AISI-304 stainless steel exterior, rear side galvanized panel
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- ACRV / ACCV double glazed door
- LED lighting
- Shelves made of plasticized steel wire, height adjustable
- AISI -304 adjustable legs, 135 to 200 mm
- Control panel and engine ventilation grill, removable
- Fan assisted condenser unit
- Fan assisted evaporator, with epoxi anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m<sup>3</sup> density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, door open and high-temperature condensation alarms. Efficient management of energy consumption
- Operating temperature 32°C ambient

OPCIONES	OPTIONS
parrilla adicional	extra shelf
set adicional guías	slides extra set
cerradura puerta cristal	glass door lock
barras carniceras	bars for meat set
set 4 ruedas	4 castors set
registrador de alarmas HACCP	HACCP alarm recorder
tropicalizado 43°C	tropicalized to 43°C
respaldo inox	stainless steel rear side
230v 60Hz / 115v 60Hz	230v 60Hz / 115v 60Hz

