

VACUUM PACKING MACHINE EXTERNAL ASPIRATION MACHINE

À EMBALLER SOUS VIDE À ASPIRATION EXTERIEURE

ENVASADORA AL VACÍO POR ASPIRACIÓN EXTERNA

VAKUUM-VERPACKUNGSGERÄTE OHNE KAMMER

MADE IN ITALY



RIAPERTURA
AUTOMATICA
AUTOMATED
REOPENING



★ PREMIUM 450

★ PREMIUM 450 AUTOMATIC

modello models modèles modelos Modelle	Dimensioni d'ingombro overall dimension dimensions d'encombrement dimensiones Abmessungen	Barra saldante sealing bar barre de soudure barra soldante Schweißleiste	Pompa del vuoto vacuum pump pompe du vide bomba de vacío Vakuumpumpe	Tensione voltage voltage tension Spannung	Assorbimento absorption absorption consumo Aufsaugen
PREMIUM 450 - INOX	470x260x130 h	mm 450	Q= 20/24 LTmin	230 V/50-60 Hz	0.45 kw
PREMIUM 450 AUTOMATIC - INOX	470x260x130 h	mm 450	Q= 40/48 LTmin	230 V/50-60 Hz	0.55 kw
PREMIUM 500 - INOX	520x260x130 h	mm 500	Q= 40/48 LTmin	230 V/50-60 Hz	0.55 kw



★ PREMIUM 500



professional
packaging