

Wall flatwork ironer ø 200

The PSE 20/140 MP FLATWORK IRONER is **the smallest model**, and enables drying-ironing of linen where space is limited.



General characteristics

- Front insertion and reception of linen.
- Roller dimensions: 1.4 metres wide and diameter of 200 mm.
- Variable-frequency drive to control ironing speed.
- Unit exterior in lacquered steel.
- Insertion and ironing belts in Nomex for easy operation, high quality ironing and great durability.
- Electronic microprocessor (speed and temperature control, auto power off function).
- Electric heating.

Note: You are recommended to insert the linen with a maximum moisture level of 45%.

MODEL (#)	CODE	ROLLER (MM) LENGTH	TABLE HEIGHT	SPEED M/MIN	PRODUCTION KG/H	POWER KW		CONNECTION EXTRACTION	DIMENSIONS MM	€
						KW.	(*)			
ROLLER Ø 200										
PS-20/140 MP	19007979	1,400	990	1÷4.5	12÷14	10.84	V	Ø 56 mm	1,878x444x1,335	-

(*) Voltage: V : Code for 400 V III+N (Optional, 230 V III)

Options

In-factory assembly on demand.

PACKAGING	FOR MODELS:	€
MARITIME wooden packaging	20/140	-

OPTIONAL VOLTAGES	FOR MODELS:	€
230 III - 50 - 60 Hz	20/140	-
MARINE - 440 III - 60 Hz	20/140	-