

High capacity

45 - 60 - 80 kg

CONCEPT General characteristics



SR-60 M E

- Easy Control Processor (M) with time and temperature control.
- External steel casing with grey coating (skinplate), stainless steel, easy to clean finish.
- Stainless steel drum.
- Axial-radial airflow, resulting in greater drying efficiency.
- Drum with stamped perforations for the gentle treatment of fabrics.
- Lint filter at the bottom, more ergonomic, larger and improved airflow.
- Automatic reverse rotation of the drum.
- Frequency inverter for smoother operation.
- Ergonomic door with a large opening and the option of double glazing.
- Anti-wrinkle system.
- End of cycle tone.
- Emergency stop button and security micro magnet to stop operation.
- Pulley and Poly-V belt transmission system with the drum supported on wheels.
- Models with high-pressure steam batteries are able to work under high pressures (up to 30 bar).

MODEL (#)	CODE (**)		CAPACITY KG		PRODUCTION KG/H	DRUM LITRES	DOOR Ø (MM)	POWER KW (*)			DIMENSIONS MM	
	STANDARD	WITH OPTIONS	(1:18)	(1:22)				HEATING	TOTAL ELECTRIC			
SR-45 M E	19071906	18003131	50	41	90	896	802	ELEC	54,00	55,90	V	1.270x1.085x2.380
SR-45 M G	19071907	18003132	50	41	90	896	802	GAS	60,00	1,90	T	1.270x1.085x2.380
SR-45 M S	19071908	18003133	50	41	90	896	802	STEAM	91,30	1,90	T	1.270x1.085x2.380
SR-60 M E	19071915	18003140	67	55	120	1.200	802	ELEC	72,00	74,00	V	1.270x1.345x2.380
SR-60 M G	19071916	18003141	67	55	120	1.200	802	GAS	90,00	2,25	T	1.270x1.345x2.380
SR-60 M S	19071917	18003142	67	55	120	1.200	802	STEAM	128,00	2,25	T	1.270x1.345x2.380
SR-80 M E	19071924	18003149	83	68	150	1.500	802	ELEC	72,00	74,65	V	1.270x1.577x2.380
SR-80 M G	19071925	18003150	83	68	150	1.500	802	GAS	120,00	2,65	T	1.270x1.577x2.380
SR-80 M S	19071926	18003151	83	68	150	1.500	802	STEAM	128,00	2,65	T	1.270x1.577x2.380

(**): STANDARD Code: Use this code for orders of machines which do not include any option or version different to standard. The retail price is as indicated in the table.
 WITH OPTIONS Code: Use this code for orders of machines which include any option or options from the table OPTIONS FOR DRYERS. The retail price is calculated by adding the price increases for each option to the retail price of the standard code.

(#): MODEL: Heating Systems (*) : Voltages : Models E - G - S: 50 Hz -Optional 60 Hz
 E: Electric Heating System by resistance. T: Code for 230 V III / 400 V III +N (Three-phase)
 G: Gas heating system With a security system and ignition system. Indicate the type of gas available (Butane, Propane, Natural, etc.). M: SINGLE PHASE Model (230 V 1+N). Can also be connected to: -230 V III (Three-phase) -400 V III +N (Three phase)
 S: Steam heating Operates using steam produced by external generators. Indicated power of the steam battery. Steam intake pressure: 6-9 bar. V: Code for 400 V III +N (Three-phase) (Optional, 230 V III) only
 FOR BOATS: Only models with electric heating. Voltage for boats 440 V III - without neutral - 60 Hz.

Options for **CONCEPT** dryers de 45 - 60 - 80 kg

NAME OF CHARACTERISTIC	CODE	ABBREVIATION	DESCRIPTION	MODEL			€
REVERSE OPENING DOOR	ZC_006_0001-0002	RD	Reverse opening door 900-1500 / STACK	45	60	80	-
STAINLESS	ZC_006_0002-0006	SSC	Casing 900	45			-
	ZC_006_0002-0007	SSC	Casing 1200		60		-
	ZC_006_0002-0008	SSC	Casing 1500			80	-
	ZC_006_0002-0023	SSF	Front 900/1200/1500	45	60	80	-
	DOUBLE GLAZED	ZC_006_0003-0002	DG	Door 550 to 1500	45	60	80
WOODEN PACKAGING	ZC_006_0006-0006	WB	Wooden packaging 900	45			-
	ZC_006_0006-0007	WB	Wooden packaging 1200		60		-
	ZC_006_0006-0008	WB	Wooden packaging 1500			80	-
STEAM BATTERY	ZC_006_0007-0004	LPB	Low pressure 900/1200/1500	45	60	80	-
VOLTAGE OPTIONS	ZC_006_0008-0015	400V 3N 60 Hz 900-1500 E/V	400V 3N 60 Hz 900-1500 E/V	45 E/S	60 E/S	80 E/S	-
	ZC_006_0008-0020	400V 3N 60 Hz 900-1500 G	400V 3N 60 Hz 900-1500 G	45 G	60 G	80 G	-
	ZC_006_0008-0040	230V 3~ 50 Hz 900-1500 G/V	230V 3~ 50 Hz 900-1500 G/V	45 G/S	60 G/S	80 G/S	-
	ZC_006_0008-0060	230V 3~ 60 Hz 900-1500 V	230V 3~ 60 Hz 900-1500 V	45 S	60 S	80 S	-
	ZC_006_0008-0065	230V 3~ 60 Hz 900-1500 G	230V 3~ 60 Hz 900-1500 G	45 G	60 G	80 G	-
	ZC_006_0008-0100	400V 3~ 50 Hz 1200-1500	400V 3~ 50 Hz 1200-1500		60	80	-
OPTIONAL FLUFF FILTER	ZC_006_0033-0002	F06	Fluff F. 0.6 (non stack)	45	60	80	-
	ZC_006_0033-0003	F12	Fluff F. 1.2 (all)	45	60	80	-
AIR INTAKE FILTER	ZC_006_0034-0001	AF	Air intake filter	45	60	80	-
EASY CONTROL SCREEN	ZC_006_0040-0001	BMS	BMS BM WITH SCREEN	45	60	80	-

Kits for **CONCEPT** dryers 45 - 60 - 80 kg

Kits available to incorporate into machines already assembled.

SAP CODE	NAME OF CHARACTERISTIC	DESCRIPTION	MODELS		
19072542	IMC	Intelligent moisture control kit	45	60	80
19072512	AF	Air inlet filter kit 45-60-80	45	60	80
12146878	-	Air inlet filter kit ø355	45	60	80
12227940	-	Programming console for Easy Control (M)	45	60	80

* Check prices at the list of accessories and spare parts.