



Catalogue :

**SERIE 900 KORE**

Chapter :

**CHARCOALS 900 KORE**

Article :

**B-E9051 I 380...415V 3N**

Code:

**19044782**

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	<b>400,00</b>	<b>1.022,00</b>
Depth	mm	<b>930,00</b>	<b>440,00</b>
Height	mm	<b>850,00</b>	<b>1.255,00</b>
Weight	kg	<b>52,00</b>	<b>65,00</b>
Volume	m3	<b>0,32</b>	<b>0,56</b>

<u>ELECTRICITY</u>	<b>380...415V</b>	<b>50/60Hz</b>	
	Power		<b>7,50 kW</b>
Connections	230 V. 1+N+T	<b>2X10MM2+T</b>	
	230 V. III+T	<b>3X4MM2+T</b>	
	400 V. III+N+T	<b>4X1,5MM2+T</b>	

GAS Not necessary

WATER Not necessary

STEAM Not necessary

AIR Not necessary

#### DESCRIPTION

ELECTRIC GRILL TOP, B-E9051 I  
The new Fagor industrial grills do not carbonize food surface and provide a healthy cooking.  
Our grills reach a very high temperature (400°C) that seals the product surface quickly and keeps a more juicy inside .  
Their new features include steam cooking.  
2 mm stainless AISI-304 steel top with rounded edges for easy cleaning.  
Laser cut and automatic welding for a perfect adjustment of sides between modules with square angle finish.  
Electric heated model with three shielded stainless steel resistances under grill surface.  
Heating control by means of power regulator.  
Stainless steel grill, 340 mm wide. Easy to remove without tools for any easy cleaning.  
Reversible grill to cook different products in a different way:  
\_ Grooved side and slanted grill for meat.  
\_ Smooth flat horizontal side for fish and vegetables  
Food gets cooked and grilled from direct contact and heat irradiation from underneath burners.  
Grill surface 24 dm2  
Fitted with a cooking fat drainage hole at the front to collect fat and grease from cooking and 12 litre collecting tray at the bottom.  
Fat collecting trays may be filled with water. Thanks to the heat irradiated by the burners a low intensity steam is produced to cook in a steam atmosphere.  
Removable 130 mm stainless steel anti splash shield, easy to wash.  
Water-tight and protecting-support controls.  
High temperature protector for the chimney made of enamelled cast iron.  
Front access to components.  
According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)  
IPX5 grade water protection equipment.  
Maximum power: 9.0 kW  
Dimensions: 400 x 930 x 850 mm.

SOUND LEVEL < 65,00 db

CERTIFICATES 99AS392

INSTALLATION - CONNECTIONS Ø  
► ELECTRICITY SI



Catalogue :  
**SERIE 900 KORE**

Chapter :  
**CHARCOALS 900 KORE**

Article :  
**B-E9051 | 380...415V 3N**

Code :  
**19044782**

# **SCHEMA - DIMENSIONS**

