



Catalogue :

SERIE 900 KORE

Chapter :

CHARCOALS 900 KORE

Article :

B-E9101 I 380...415V 3N

Code:

19044785

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	800,00	1.022,00
Depth	mm	930,00	840,00
Height	mm	850,00	1.265,00
Weight	kg	52,00	65,00
Volume	m3	0,63	1,09

<u>ELECTRICITY</u>		<u>50/60Hz</u>	
	380...415V		
Power			15,00 kW
Connections	230 V. 1+N+T	2X16MM2+T	
	230 V. III+T	3X10MM2+T	
	400 V. III+N+T	4X4MM2+T	

GAS Not necessary

WATER Not necessary

STEAM Not necessary

AIR Not necessary

DESCRIPTION

ELECTRIC GRILL TOP, B-E9101 I
 The new Fagor industrial grills do not carbonize food surface and provide a healthy cooking.
 Our grills reach a very high temperature (400°C) that seals the product surface quickly and keeps a more juicy inside .
 Their new features include steam cooking.
 2 mm stainless AISI-304 steel top with rounded edges for easy cleaning. Laser cut and automatic welding for a perfect adjustment of sides between modules with square angle finish.
 Electric heated model with two groups of three shielded stainless steel resistances under grill surface.
 Independent power regulator for each electrical resistance group.
 Stainless steel grill with two 340 mm wide sections. Easy to remove without tools for any easy cleaning.
 Reversible grill to cook different products in a different way:
 _ Grooved side and slanted grill for meat.
 _ Smooth flat horizontal side for fish and vegetables
 Food gets cooked and grilled from direct contact and heat irradiation from underneath burners.
 Grill surface 48 dm2
 Fitted with two cooking fat drainage holes at the front to collect fat and grease from cooking, and 12 litre collecting trays at the bottom. Fat collecting trays may be filled with water. Thanks to the heat irradiated by the burners a low intensity steam is produced to cook in a steam atmosphere.
 Removable 130 mm stainless steel anti splash shield, easy to wash.
 Water-tight and protecting-support controls.
 High temperature protector for the chimney made of enamelled cast iron.
 Front access to components.
 According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)
 IPX5 grade water protection equipment.
 Maximum power: 18.0 kW
 Dimensions: 800 x 930 x 850 mm.

SOUND LEVEL < **65,00** db

INSTALLATION - CONNECTIONS Ø
 ► ELECTRICITY SI



Catalogue :
SERIE 900 KORE

Chapter :
CHARCOALS 900 KORE

Article :
B-E9101 | 380...415V 3N

Code :
19044785

SCHEMA - DIMENSIONS

