

Catalogue :

SERIE 900 KORE

Chapter : RANGES 900 KORE

Article :

C-E920 380...415V 3N

Code: 19031224

| 19031224 | | | | | |
|-----------------------------|----------------|----------------|-------------------|---|--|
| DIMENSIONS AND WEIGHTS | | Net dimensions | Packed | DESCRIPTION | |
| Length | mm | 400,00 | 1.022,00 | 2-HOT PLATES ELECTRIC BOILING TOP, C-E920 | |
| Depth | mm | 930,00 | 440,00 | Electric top plates are adequate for a variety of containers such as | |
| Height | mm | 290,00 | 535,00 | pans, saucepans, etc. Depending on the container, you may stew, boil, make soup, legumes, | |
| Weight | kg | 40,00 | 55,00 | scrambled eggs, fried dishes | |
| Volume | m3 | 0,11 | 0,24 | 2 mm stainless AISI-304 steel embedded top with rounded edges for easy cleaning. | |
| Volume | ino | 0,11 | 0,24 | Laser cut and automatic welding for a perfect side to side adjustment of modules with square angle finish. | |
| ELECTRICITY | 380415V | 50/60Hz | | 4 kW power 300 x 300 mm cast iron heating plates tight adjusted to the | |
| | Power | | 8,00 kW | embedded top stove. Number of plates: 2. Power adjustment by 7-position knob. Independent safety thermostat for | |
| Connections | 230 V. 1+N+T | 2X2,5 + T | | each plate. | |
| | 230 V. III+T | 3X10+T - 63 | 3 A | Inner fan to reduce the temperature of the components. | |
| | 400 V. III+N+T | 4X1,5MM2+ | ۲ | Water-tight and protecting-support controls. High temperature protector for the chimney made of enamelled cast iron. Front access to components. | |
| GAS | Not necessary | | | According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203) IPX5 grade water protection equipment. Maximum power: 8.0 kW | |
| | | | | Dimensions: 400 x 930 x 290 mm. | |
| <u>WATER</u> | Not necessary | | | | |
| | | | | | |
| | | | | | |
| STEAM | Not necessary | | | | |
| | | | | | |
| | | | | | |
| AIR | Not necessary | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| SOUND LEVEL | | | < 65,00 db | | |
| | | | | | |
| | | | | | |
| INSTALLATION - CONNECTIONSØ | | | Ø | | |
| | ► ELECTRICITY | SI | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |






Catalogue : SERIE 900 KORE Chapter :


RANGES 900 KORE

Article : C-E920 380...415V 3N

Code : 19031224


SCHEMA - DIMENSIONS





<u>C-E940</u>

<u>C-E920</u>



- E. Conexión eléctrica 1. Mando placas M
- Electrical connection M plates control