

Catalogue  
**CATERING**

Chapter  
**COOKING**

Model  
**C-GE941 LPG 380...415V 3N**

19044988



**DIMENSIONS**

	<b>Article</b>		<b>Packed</b>	
Lenght	800	mm	840	mm
Depth	930	mm	1022	mm
Height	850	mm	1125	mm
Weight	149,000	kg	165,000	kg
Volume	0,632	m3	0,966	m3

**ELECTRICITY**

Electric power	6,00	kw
Voltage	380...415V	-3N
Three-phase 230V wiring	3X2,5+T	- 20A
Frequency	50/60	hz

**GAS**

Power	28,70	kw
	24699,58	kcal/h
LPG Consumption	2,39	kg/h
Pressure	LPG G30/G31	28-30/37 mbar

**Certification EQNET-CE**

1312CS6219

**4-BURNER GAS RANGE ON ELECTRIC OVEN, C-GE941**

Top burners are adequate for a variety of containers such as frying pans, saucepans, pots, etc.

Depending on the container, you may stew, boil, make soup, legumes, scrambled eggs, fried dishes...

Using the optional plate (easy to place on any of the grids) you may grill meat, fish, sea food or vegetables at any moment.

2 mm thick AISI-304 stainless steel embedded top. Each half module (two burners) is fitted with an integrated 1 litre liquid-collecting container.

Laser cut and automatic welding for a perfect side to side adjustment of modules with square angle finish.

Machine with four burners of different power for a variety of containers and to provide different ways to cook different types of food: (2 x 5.25) + 8.0 + 10.2 kW

Double crown nickel-plated cast iron burners and diffusers to ensure an even distribution of heat and flame on pans' bottom, even on those of large dimensions.

This prevents the concentration of heat at one single spot and optimizes power transfer to the product.

Burner and diffuser parts easy to remove and dismantle for cleaning.

Unequivocal position of the burner assembly and placement.

397 x 350 mm grid for large size pans and frying pans.

75 mm distance between central spokes to support small dimension pans (8 ÷ 9 cm). This provides a safe stand for small containers.

The grids are made of RAAF enamelled cast iron (resistant to alkaline, acid products ant to fire and high temperatures). Easy to remove and washable.

Low consumption pilots and thermocouples inside the burner's body for a more efficient protection.

**GN-2/1 OVEN**

Easy to use GN 2/1 size oven, with controls at the top.

Fully stainless steel cooking chamber, for easy cleaning and higher hygienic standards.

Wide side insertion tray for an enhance manoeuvrability.

Three level guides to provide different working options.

Thermostatic valve for temperature control (125 - 310°C).

Heated by shielded stainless steel electrical resistances with a top or lower zone selector.

Total heating power: 6 kW

6 mm thick cast iron bottom to ensure a better performance and an even distribution of heat.

Fibreglass seal for an enhance thermal efficiency of the oven.

Removable door for easy maintenance.

Water-tight and protecting-support controls.

High temperature protector for the chimney made of enamelled cast iron.

Front access to components.



FAGOR INDUSTRIAL

Catalogue  
**CATERING**

Chapter  
**COOKING**

Model  
**C-GE941 LPG 380...415V 3N**

19044988

According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)

IPX5 grade water protection equipment.



FAGOR INDUSTRIAL

Catalogue  
**CATERING**

Chapter  
**COOKING**

Model  
**C-GE941 LPG 380...415V 3N**

19044988