

# MIWE

## MIWE roll-in e+

### MIWE roll-in e+ for one rack trolley

Economical with energy consumption, and best baking results even with batch-after-batch baking. This characterized the MIWE roll-in e+.

Rack trolley	1
Baking tray size	80/60 60/80 60/100 per 2 items 53/65
Baking area in sq m	9,6 - 15,2
Rotary table	yes
Width outside in cm	155/182
Depth outside in cm	160/185
Height outside in cm	256 - 272(*)
Minimum ceiling height in cm	285 - 301
Type of energy transmission	Convection
Heating mode	Oil, gas, electrical
Control system	Fixed program control MIWE FP10 or Touch Control MIWE TC
Connected load in kW	60 - 95
Special features	Air quantity regulation MIWE aircontrol (patented), flexbake (partial loading), frozen small product control, CAB

\* Suitable for all rack trolleys heights up to 1980 mm



► [Request information](#)

## MIWE roll-in for two rack trolleys

The MIWE roll-in e+ for two rack trolleys with double the space for high throughput.

Rack trolley	2
Baking tray size	60/80 80/100
Baking area in sq m	17,3 - 21,6
Rotary table	yes
Width outside in cm	216/226
Depth outside in cm	229
Height outside in cm	295
Minimum ceiling height in cm	335
Type of energy transmission	Convection
Heating mode	Oil/gas
Control system	Fixed program control MIWE FP10 or Touch Control MIWE TC
Connected load in kW	130 - 140



► [Request information](#)

© Copyright: MIWE Michael Wenz GmbH, 2007