

Modular Cooking – Grandis 900 Electric Induction Cooker NEIC 4-90 GR



*Due to routine technical improvement, the photograph shown may not represent the latest design of the products.

AVAILABLE MODEL

1. NEIC 4-90 GR

DESCRIPTION

Electric Induction Cooker with 10 kW power rate and surface with 2 independently controlled 5 kW induction zones. Induction top surface with seamless transition between individual heating zones.

Unit to be installed on open cabinet or similar elements, cantilever, or solid block solutions. Featuring removable clip joint to connect Grandis family product.

ITEM#	:
MODEL#	:
NAME	:

MAIN FEATURE

SN

- Glass ceramic surface with 2 independently controlled induction zones with 5 kW power rate per zone.
- Heating with circular coil with coil diameter of 220 mm.
- Unit to be installed free standing, can be joined with base cabinet, table stand or cantilever system.
- Service maintenance can be done from the front panel.

CONSTRUCTION

- All exterior panels in 304 type of Stainless Steel
- Orbital top panel anti-scratch finishing.
- Top with 2.0 mm thick surface.
- Side with 0.8 mm thick surface.
- Adjustable ±25 mm Stainless Steel leg.


INCLUDED ACCESSORIES


N/A

OPTIONAL ACCESSORIES

Clip Plate for Joining

FRONT 400 ◮ **TOP**





ELECTRIC

Electrical rating (kW) 10 kW Element rating (kW) 10 kW : Electrical supply voltage 380V 3N

Required electrical supply (amps): 24

Electrical current split (amps): L1: 24

L2: 24

L3: 24

KEY INFORMATION

Cooking surface width 350 mm

Cooking surface depth 650 mm :

Direct heat emission 1.12 kW

0.44 kW Latent heat emission

Steam emission 0.66 kg / h

Net weight

Shipping height 1020 mm

Shipping width 455 mm

Shipping depth 994 mm

Shipping volume 0.461 m³