

The perfect balance between quality and price.

Concept range machines are designed for those looking for the best, but with simple operation, without complications and easy maintenance. Models are equipped with high-quality functions as standard and they include EASY control.



Low and medium capacity

11 - 16 - 23 - 28 - 35 kg

Analogue control



CONCEPT General characteristics

- Easy Control Processor (M) with time and temperature control.
- External steel casing with grey coating (skinplate), stainless steel, easy to clean finish.
- Stainless steel drum.
- Axial-radial airflow, resulting in greater drying efficiency.
- Drum with stamped perforations for the gentle treatment of fabrics.
- Lint filter at the bottom, more ergonomic, larger and improved airflow.
- Automatic reverse rotation of the drum.
- Frequency inverter for smoother operation.
- Ergonomic door with a large opening and the option of double glazing.
- Anti-wrinkle system.
- End of cycle tone.
- Emergency stop button and security micro magnet to stop operation.
- Motion transmission by geared motor on models up to 23 kg, by pulley and Poly-V belts with the drum supported by wheel on models between 28 and 35 kg.

OPTION

- Optional screen to view time, temperature and programme (3 possible programmes). The technical menu can also be accessed without having to use the console.

MODEL (#)	CODE (**)		CAPACITY KG		PRODUCTION KG/H	DRUM LITRES	DOOR Ø (MM)	POWER KW (*)			DIMENSIONS MM	
	STANDARD	WITH OPTIONS	(1:18)	(1:22)				HEATING	TOTAL ELECTRIC			
SR-11 M E	19071857	18003080	12	10	21	210	574	ELEC	12	12,55	V	785x840x1.694
SR-11 M G	19071858	18003081	12	10	21	210	574	GAS	20,5	0,55	M	785x840x1.694
SR-11 M S	19071859	18003082	12	10	21	210	574	STEAM	30	0,55	M	785x840x1.694
SR-16 M E	19071868	18003091	18	15	33	330	574	ELEC	18	18,55	V	785x1.110x1.694
SR-16 M G	19071870	18003092	18	15	33	330	574	GAS	20,5	0,55	M	785x1.110x1.694
SR-16 M S	19071871	18003093	18	15	33	330	574	STEAM	30	0,55	M	785x1.110x1.694
SR-23 M E	19071880	18003102	26	21	46	460	574	ELEC	24	24,97	V	890x1.245x1.812
SR-23 M G	19071361	18003103	26	21	46	460	574	GAS	31	0,97	M	890x1.245x1.812
SR-23 M S	19071881	18003104	26	21	46	460	574	STEAM	49,2	0,97	M	890x1.245x1.812
SR-28 M E	19071890	18003113	31	25	55	550	802	ELEC	30	31,15	V	985x1.054x1.946
SR-28 M G	19071891	18003114	31	25	55	550	802	GAS	41	1,15	M	985x1.054x1.946
SR-28 M S	19071892	18003115	31	25	55	550	802	STEAM	50,1	1,15	M	985x1.054x1.946
SR-35 M E	19071899	18003122	37	30	66	660	802	ELEC	36	37,15	V	985x1.210x1.946
SR-35 M G	19071900	18003123	37	30	66	660	802	GAS	41	1,15	M	985x1.210x1.946
SR-35 M S	19071901	18003124	37	30	66	660	802	STEAM	50,1	1,15	M	985x1.210x1.946

(**) STANDARD Code: Use this code for orders of machines which do not include any option or version different to standard. The retail price is as indicated in the table.
 WITH OPTIONS Code: Use this code for orders of machines which include any option or options from the table OPTIONS FOR DRYERS. The retail price is calculated by adding the price increases for each option to the retail price of the standard code.

(#):	MODEL: Heating Systems	(*) :	Voltages :	Models E: 50 Hz -Optional 60 Hz Models G - S: 50 Hz - 60 Hz
E :	Electric Heating System by resistance.	T :	Code for 230 V III / 400 V III +N (Three-phase)	
G :	Gas heating system With a security system and ignition system. Indicate the type of gas available (Butane, Propane, Natural, etc.).	M :	SINGLE PHASE Model (230 V 1+N). Can also be connected to: -2 V III (Three-phase) -4 V III +N (Three phase)	
S :	Steam heating Operates using steam produced by external generators. Indicated power of the steam battery. Steam intake pressure: 6-9 bar.	V :	Code for 400 V III +N (Three-phase) (Optional, 230 V III) only	
		FOR BOATS:	Only models with electric heating. Voltage for boats 440 V III - without neutral - 60 Hz.	